


## DATASHEET



cutout · Ø70  
 Ø · 78  
 h · 88



DIALux

### KLIKLED® DOWNLIGHTS

| KDL50C                |     |     |    |               |     |     |
|-----------------------|-----|-----|----|---------------|-----|-----|
| Optics                |     |     |    | Reflector     |     |     |
| Beam Angle            |     |     |    | NSP           | SP  | NFL |
| LOR defined by optics |     |     |    | 82            | 81  | 80  |
| lm                    | W   | mA  | V  | System Lumens |     |     |
| 360                   | 2.8 | 250 | 12 | 295           | 290 | 285 |
| 495                   | 3.9 | 350 | 12 | 410           | 405 | 400 |
| 675                   | 5.7 | 500 | 12 | 555           | 550 | 540 |
| 900                   | 8.2 | 700 | 12 | 740           | 730 | 720 |

NSP - narrow spot 10-19° · SP - spot 20-34° · NFL - narrow flood 35-49°

|                       |  |
|-----------------------|--|
| Colour                | 3000K · 4000K · 5000K                              |
| CRI                   | 80-85  |
| Binning               | 2 McAdam Step                                      |
| Control               | Non Dim · DALI · 0-10V                             |
| Weight/Pack Size      | 0.125kg - 140 x 140 x 140mm                        |
| Cutout Size           | Ø 70 +3/-0mm                                       |
| Finish (ceiling trim) | clear anodised · white powder coat · custom colour |

KDL-50C-20160919-01