



DATA SHEET



DIRECT	LEDoptek					
LED lumens/m	-	1000	1500	2250	3350	4500
Delivered Lumens/m ¹	-	721	1082	1622	2246	3245
Standard CRI	>90					
INDIRECT						
LED lumens/m	500	1000	1500	2250	3350	4500
Delivered Lumens/m ¹	405	810	1215	1823	2524	3260
Standard CRI	>90					
System W/m						
2700K	4.6	10.8	17.3	24.8	36	43.2
3000K	4.4	9.1	15.8	23.5	34.5	41
3500K	4.3	9.1	15.8	23.4	34.5	41
4000K	4.2	9.7	14	22.7	33.4	38.9
Other LED Options	5000K · RGBW · tuneable white · cyanosis · high CRI 98 R9 > 80					
Control	non dim · DALI · Casambi · 0-10V · DMX					
Optics	LEDoptek - asymmetrical					
Finish	white/black/silver powder coat standard · custom powder coat · clear anodised					
Weight/Pack Size	5.2kg/m - 130 x 190 x (l + 200mm)					
Mounting	wall mount bracket · full bracket up to 1.2m · Individual brackets over 1.2m					
Accessories	mitred bends · patient night light and local rocker · integrated patient nurse call systems · patient pull cord switch · sensor · others available					
Luminaire Length	any length over 500mm with fully illuminated diffuser					

1. Lumens based on LEDoptek - asymmetrical optics

MED080EDI-LEDoptek-20210531-01

